

The CAM2 logo is located in the top right corner of the page. It features the letters 'CAM2' in a bold, italicized, red font with a white outline and a black drop shadow, set against a background of a checkered flag and a red and orange wavy graphic.

PRODUCT BULLETIN

SuperPro MAX Synthetic Blend Motor Oil 5W-20

API SN and SN-RC and ILSAC GF-5

PRODUCT #408

CAM2 SUPERPRO MAX Motor Oils are fully licensed to meet or exceed the latest automotive manufacturers' requirements of API SN and SN-RC. **CAM2 SuperPro MAX 5W-20, 5W-30, and 10W-30** are fully licensed to meet and exceed ILSAC GF-5 requirements for use in passenger car, SUV and light duty truck gasoline engines. **CAM2 SuperPro MAX Motor Oils** show improved high temperature deposit control, oil consumption and fuel economy. **CAM2 SuperPro MAX 5W-20, 5W-30, 10W-30, 10W-40 and 20W-50** are synthetic blend premium motor oils that provide better low temperature pumpability and protection.

CAM2 SuperPro MAX Motor Oils are premium quality motor oils formulated from selected superior base oils and advanced additive technology, providing the highest levels of equipment protection available. **CAM2 SuperPro MAX motor oils** are the engine oils of choice for passenger cars, light trucks, powerboats, motorcycles, and other stationary and mobile equipment.

FEATURES

CAM2 SuperPro MAX Motor Oils provide:

- Excellent Fuel Economy
- Excellent volatility for low oil consumption
- Excellent protection from deposits at all operating temperatures
- Excellent cold-cranking capabilities
- Excellent anti-wear, anti-foam, bearing corrosion and anti-rust protection
- Advanced varnish & sludge protection
- Superior Synthetic Blend Protection against thermal breakdown (5W-20 & 5W-30)
- Meets or exceeds API Resource Conserving (RC) standards (5W-20, 5W-30, 10W-30) ILSAC GF-5 Certified (5W-20, 5W-30, 10W-30)

See Technical Data on pg 2.



CAM2 INTERNATIONAL, LLC

211 Violet Street Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

www.CAM2.com



PRODUCT BULLETIN

SuperPro MAX Synthetic Blend Motor Oil 5W-20

API SN and SN-RC and ILSAC GF-5

PRODUCT #408

APPLICATIONS

CAM2 SuperPro MAX Motor Oils meet current and previous API service classifications: **API SN, SM, SL, SJ, SH, SG, SF** and **ILSAC GF-5, GF-4, GF-3, GF-2 & GF-1** on applicable viscosity grades. **CAM2 SuperPro MAX Motor Oils** are recommended for the following uses:

- When Ford WSS-M2C945-A or WSS-M2C946-A is specified
- When Chrysler MS-6395S is specified

CAM2 SuperPro MAX Motor Oils are available in 5 multi-viscosity grades to comply with most passenger car and light duty truck engine applications. Two single-viscosity grades are also available. Follow equipment manufacturer recommendations for specific applications.

- For GM Vehicles model years 2011 and after, see our CAM2 dexos1™ full synthetic motor oil.

TECHNICAL DATA

SAE GRADE	5W-20	5W-30	10W-30	10W-40	20W-50	SAE 30	SAE 40
Product Code	408	409	414	416	417	419	420
Viscosity @ 40°C, cSt	49.21	63.01	68.23	105.68	153.05	86.11	123.33
Viscosity @ 100°C, cSt	8.59	10.57	10.49	15.26	18.29	11.11	13.97
Viscosity, SUS @ 210°F	54.38	61.25	60.96	78.95	91.29	63.18	73.89
Viscosity Index	153	158	141	152	134	116	111
API Gravity	32.78	33.01	31.51	31.74	29.77	29.97	29
Pour Point: °C	-48	-48	-42	-42	-36	-33	-24
API: RC (Resource Conserving):	YES	YES	YES	NO	NO	NO	NO
ILSAC GF-5 Certified:	YES	YES	YES	NO	NO	NO	NO
Color	3	3	3	3	3.5	3	3
API Licensed Service:	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ	SN, SM, SL, SJ

Contact your CAM2 representative or CAM2 distributor for additional information.

CAM2 INTERNATIONAL, LLC

211 Violet Street Suite 100 • Golden, CO 80401

Telephone 800/338-2262 • Fax: 303/679-8988

www.CAM2.com