

LUBRICANTS

2-STROKE
SYNTHETIC



SNOWMOBILE TECHNIPLATE® TC-W3

Mastering the Science of Synthetic Lubrication

Premium pure synthetic lubricant. Extremely high load carrying capacity for reduced engine wear and low maintenance. Clean Burn No-Smoke Technology eliminates carbon and residue build-up. Use of this lubricant provides certified warranty compliance and protection. Meets and exceeds API TC, TC-W, TC-W3, JASO FD and ISO-EGD specifications for certified warranty compliance in Ski-Doo, Polaris, Yamaha and Arctic Cat Snowmobiles.

- Super Cold Pour Point of -40F provides fast, easy starting.
- TechniPlate Peak Film Strength and Anti-Scuff protection
- High Load Carrying Capacity for reduced engine wear
- Clean Burn™ Technology reduces carbon and residue build-up
- Ashless, No-Smoke formula provides cleaner exhaust
- Contains familiar Klotz Red for easy mixing and racy odor
- Anti-Oxidation protection against hand corrosion
- Power Valve formula for R.A.V.E.™, V.E.S.™, A.P.V.™ and Y.P.V.S™ Valve engines

▶ APPLICATION:

Snowmobile - 2-stroke/gas; Stock/trail, Hi-performance, Drag Racing, Snow Cross, Water Cross

▶ CHARACTERISTICS:

Smoke Rating:	10	1=fog; 10=no smoke
Clean Burn™:	10	1=heavy deposits; 10=no carbon
Film Strength:	8	1=failure; 10=virtually no wear
Viscosity @100C:	7.1 cSt	
Pour Point:	-40F	
Flash Point:	215F	
RPM Limit:	10,000	
Ash Content:	None	
Rust Prevention:	Contain rust inhibitors. Excellent storage lubricant.	
Certification:	Klotz Certified warranty compliant when a JASO FD, ISO-EGD, API TC or TC-W3 lubricant is required, including Ski-Doo, Polaris, Arctic Cat and Yamaha.	

Color: Red

▶ DIRECTIONS:

Compatibility: Blends with gasoline and stays in suspension. Will blend with petroleum oils and synthetic lubricants 48% Biodegradable formula.

Fuel Stability: Will dissolve in gasoline at ratios of 15:1 or greater.

2-Stroke pre-mix or injection:

Snowmobile: Mix at 40:1 to 50:1

▶ AVAILABILITY: KL-215 quart; KL-216 gallon; 30 & 55 gallon drum



ADVANCED WARRANTY PROTECTION
TC-W3 JASO FD ISO-EGD
POWER VALVE FORMULA

TECHNIPlate
Advanced Lubrication System

-40
COLD FLOW

R.A.V.E.™ is registered trademark of Bombardier Inc.