



PRODUCT INFORMATION

a product of NITEO™ Products

PYROIL™ STARTING FLUID

DESCRIPTION:

Pyroil Starting Fluid has been formulated to deliver maximum starting strength. Ether and petroleum distillates are blended together to produce a starting fluid which has a low freezing point, high vapor pressure (produces vapor at low temperatures which passes through air intake systems and air filters), low flash point (ignition), high BTU content (starting power) and an upper cylinder lubricant for protection.

Extensive testing using a diesel engine in sub-zero temperatures has shown an optimum ether content range exists. Starting fluids containing too much or too little ether failed to start a diesel engine at cold temperatures. **Pyroil Starting Fluid** gives maximum starting strength by carefully controlling ether content.

For fast, easy starting, spray **Pyroil Starting Fluid** into the air intake for 2-3 seconds (no more than 3 seconds), and then start the engine. Besides cars and trucks, **Pyroil Starting Fluid** works great on lawn mowers, trimmers, chain saws, motorcycles, etc. (not necessary to remove air filter).



Part Number	Description	Unit UPC
PYSFR7.5	Pyroil Starting Fluid 12/7.5 oz.	0 28882 10072 4
PYSFR11	Pyroil Starting Fluid 12/11 oz.	0 28882 10074 8

BENEFITS:

- Starts Engines Quickly and Reduces Drain On Batteries
- Starts Diesel Or Gasoline Engines
- Contains An Upper Cylinder Lubricant
- Fits Diesel Injector Systems
- Gives Smooth Starts In All Kinds Of Weather

FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:
12/1/2014	12/1/2019	3/1/2011	DET	2

All information herein is believed to be true and correct, but is not to be taken as a representation or warranty, express or implied, including any warranty with respect to merchantability or fitness for any particular purpose. ™Trademark, Niteo, registered in various countries. ©2015, Niteo.



PRODUCT INFORMATION

a product of NITEO™ Products

TECHNICAL DATA:

Appearance	Clear Liquid Aerosol
Flash Point, °F	-49 °F / -45 °C
Density	0.7114 g/cm ³ @ 77 °F / 25 °C
Plastic Safe	No
Propellant	Carbon Dioxide
Boiling Point	94.3 °F / 34.6 °C
Aerosol Flammability Level	III
VOC Category	NA
VOC/Regulatory Restrictions	None / Extremely Flammable
Note	Use outdoors with adequate ventilation

FOR MORE INFORMATION, VISIT WWW.NITEOPRODUCTS.COM OR CALL 844-696-4836

This information applies only to products manufactured in the following location(s): USA, Canada

Effective Date:	Expiration Date:	Replaces:	Author's Initials:	Pages:
12/1/2014	12/1/2019	3/1/2011	DET	2

All information herein is believed to be true and correct, but is not to be taken as a representation or warranty, express or implied, including any warranty with respect to merchantability or fitness for any particular purpose. ™Trademark, Niteo, registered in various countries. ©2015, Niteo.