



Warren® GL-5 Gear Oils

Warren GL-5 Gear Oils are multi-purpose sulfur/phosphorous gear lubricants designed for API Service Classification “GL-5”.

Warren GL-5 Gear Oils are compounded with highly refined base stocks and additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust preventions, low pour point, and anti-foaming performance. Can be used in limited slip differentials for top-off only.

Warren GL-5 Gear Oils are recommended for use in conventional differentials of cars, pick up trucks and sport utility vehicles. Always check owner’s manual for proper recommendation.

Benefits

- Excellent wear protection
- Shear resistant
- Excellent rust and corrosion protection
- Excellent Demulsibility, separates water readily
- Limited Slip for top-off only



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Warren® GL-5 Gear Oils

Typical Characteristics

Warren GL-5 Gear Oil		
	80W-90	85W-140
SAE Viscosity Grade	80W-90	85W-140
Pour Point Deg F.	-15	+5
Flash Point, COC, °F	420	430
Viscosity		
@ 40°C, cSt	140	345
@100°C, cSt	14.6	26.3
Viscosity Index	95	95
Gravity, API	26.0	26.3
Rust Test, ASTM D665	Pass	Pass
Product Code #		
Bulk	12200	12300
Drum	WARGRLUB80W9055	WARGRLUB85W14055
Keg	WARGRLUB80W90120	WARGRLUB85W140120
Pail	WARGRLUB80W905	WARGRLUB85W1405
Case, 6/1 Gallon	WARGRLUB80W906	WARGRLUB85W1406
Case, 12/1 Quart	WARGRLUB80W9012	WARGRLUB85W14012



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301